



Ravi®

CROSS SHAFT RNX

MODEL		UNITS	RNX-35			RNX-45			RNX-63			RNX-80		RNX-110		RNX-160		RNX-200		RNX-250	
TYPE			UGS	HSG	SGS	UGS	HSG	SGS	UGS	HSG	SGS	HSG	SGS	HSG	SGS	HSG	SGS	HSG	SGS	HSG	SGS
CAPACITY		TONNE	35			45			63			80		110		160		200		250	
STROKE LENGTH	FIX	MM	40	40	90	50	50	110	50	50	130	60	150	70	160	80	200	90	220	100	250
	VARIABLE	MM	8~40	8~40	8~80	8~50	8~50	8~90	8~50	8~50	8~100	8~60	8~100	8~70	8~125	-	8~160	-	20~220	-	20~160
SPEED	FIX	SPM	150	130	80	140	120	70	130	100	60	100	60	80	50	80	40	80	35	55	60
	VARIABLE	SPM	100~200	80~170	60~90	100~180	80~160	50~80	100~180	70~150	40~70	60~130	40~70	60~120	35~60	50~100	30~50	50~100	25~45	30~70	25~40
RATING POINT		MM	1.2	2.3	3.2	1.5	2.3	3.2	1.5	2.3	4	3	4.5	3	5	3.5	6	3.5	6	4	6
SHUT HEIGHT (SDAU)		MM	250			270			320			350		380		420		450		48	
SLIDE ADJUSTMENT		MM	50			60			70			80		90		100		110		120	
SLIDE AREA		MM²	380x300			430x350			500x400			560x460		650x520		720x580		86x650		960x720	
BOLSTER AREA		MM²	780x400			800x440			900x550			1050x600		1150x700		1250x760		1400x840		1500x900	
BOLSTER THICKNESS		MM	85			110			120			140		140		160		180		180	
FLOOR TO BOLSTER		MM	800			800			860			900		900		900		1000		1000	
MAIN MOTOR	FIX	HP x P	3x4			5x4			7.5x4			10x4		10x4		15x4		20x4		25x4	
	VARIABLE		5x4			7.5x4			10x4			15x4		15x4		20x4		25x4		30x4	
DIE CUSHION																					
CAPACITY		TONNE	3.5			3.5			6			6		8		10		14		14	
STROKE LENGTH		MM	50			50			70			70		90		100		110		120	
PRESSURE PAD AREA		MM	300x210			300x210			380x260			410x260		480x300		450x340		640x440		740x540	
			UGS : UNGEARED SERIES			HSG : HIGH SPEED GEARED SERIES			SGS : STANDARD GEARED SERIES												



RAVI INDUSTRIAL CORPORATION

38-A, Industrial Area-A Extension,
Ludhiana-141 003. (Punjab) INDIA

Tel. : +91-161-5016832, 4618552
Mobile : +91-98153-00435, 97797-00025

E-mail : info@ravipresses.com
Website : www.ravipresses.com