



Friction
Screw Press

Ravi Industrial Corporation

Specification of : Friction Screw Press

Capacity	30	50	100	200	300	400	500
Dia of Screw	3.1/4"	4"	5"	6"	8"	9"	11"
Stroke of Press	7"	8"	11"	14"	16"	18"	20"
Table to Side (Max.)	13"	14"	18"	22"	25"	28"	32"
Table to Side (Min.)	6"	6"	7"	8"	9"	10"	12"
Size of Table (Front)	12"	15"	19"	23"	26"	29"	30"
Size of Table (Side)	11"	14"	18"	21"	24"	28"	30"
Distance Table to Guides	6"	6"	8"	10"	12"	14"	16"
Distance Between Columns	13"	16"	20"	23"	26"	30"	32"
Distance Between Guides	9"	12"	14"	17"	19"	22"	24"
Bore in Table	3"	3"	4"	5"	6"	7"	7"
Bore in Ram (Shank Dia)	1.1/2"	1.1/2"	2"	2.1/2"	3"	3"	4"
Dimensions of Ram	9"x9"	12"x12"	14"x14"	17"x17"	19"x19"	21"x22"	24"x24"
T Slots in Table	5/8"	5/8"	5/8"	5/8"	3/4"	1"	1".1/4"
T Shots in Ram	5/8"	5/8"	5/8"	5/8"	3/4"	1"	1"
H.P. Required	5 H.P.	7.5 H.P.	10 H.P.	20 H.P.	30 H.P.	40 H.P.	50 H.P.
RPM	1440	1440	1440	1440	1440	1440	1440
Approx. Weight in Kgs.	2000	3000	5000	9000	13000	17000	23000



Ravi Industrial Corporation

38-A, Industrial Area-C, Ludhiana-141 010 (Punjab) INDIA Tel. : +91-161-5016832, 4618552

Mobile : 98153-00435, 97797-00025 E-mail : info@ravipresses.com

Website : www.ravipresses.com